

**OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910. 1200  
MATERIAL SAFETY DATA SHEET**

<b>IDENTITY</b> <i>As Used on Label and List</i>		<b>"RECOVERY/SURGICAL SUITE" ABSORBENT PADS</b>											
<b>SECTION I</b>													
Manufacturer's name			Emergency telephone number										
Address (Number, Street, City, State and Zip Code)			Telephone Number for Information										
			Date Issued - Revised <b>10/19/2009</b>										
			Signature of Preparer (optional)										
<b>SECTION II – Hazardous Ingredients / Identity Information</b>													
Hazardous Components (Specific Chemical Identity / Common Name (s))		OSHA-PEL	ACGIH TLV	Other Limits Recommended	% (optional)								
<b>CROSS-LINKED POLYACRYLATE POLYMER OR POLYACRYLATE POLYMER – ABSORBENTS.</b>		<b>NONE EST.</b>	<b>NONE EST.</b>	<b>N/A</b>	<b>N/A</b>								
<b>POLYPROPYLENE FIBERS/NONWOVENS</b>		<b>NONE EST.</b>	<b>NONE EST.</b>	<b>N/A</b>	<b>N/A</b>								
<b>CELLULOSE TISSUE</b>		<b>NONE EST.</b>	<b>NONE EST.</b>	<b>N/A</b>	<b>N/A</b>								
RECOMMENDED EXPOSURE GUIDELINE:													
<b>0.05 MG/M3 RESPIRABLE PARTICULATE</b>		<table border="1"> <tr><td>1</td><td>Health</td></tr> <tr><td>1</td><td>Flammability</td></tr> <tr><td>1</td><td>Reactivity</td></tr> <tr><td>E</td><td>Protective Equipment</td></tr> </table>				1	Health	1	Flammability	1	Reactivity	E	Protective Equipment
1	Health												
1	Flammability												
1	Reactivity												
E	Protective Equipment												
<b>SECTION III – Physical /Chemical Characteristics</b>													
Boiling Point		N/A	Specific Gravity (H <sub>2</sub> O=1)		N/A								
Vapor Pressure (mm Hg.)		N/A	Melting Point		N/A								
Vapor Density (AIR=1)		N/A	Evaporate Rate (Butyl Acetate=1)		N/A								
Solubility in Water	SLIGHT- CONTAINS SMALL AMOUNT OF WATER EXTRACTABLE MATERIAL												
Appearance and Odor	WHITE COLOR PAPER (SOME GRADES MAY BE COLORED) – NO ODOR												
<b>SECTION IV – Fire and Explosion Hazard Data</b>													
Flash Point (Method Used)	N/A	Flammable Limits	NO SPECIFIC INFO.	LEL	N/A	QEL	N/A						
Extinguishing Media	WATER, FOAM OR SAND CAUTION: PADS WILL ABSORB WATER AND BECOME SLIPPERY WHEN WET.												
Special Fire Fighting Procedures	WEAR SELF-CONTAINED POSITIVE BREATHING APPARATUS & FULL FIRE-FIGHTING PROTECTIVE CLOTHING.												
Unusual Fire and Explosion Hazards	PADS MAY CONTAIN POLYOLEFIN COMPONENTS. HEATING CAN CAUSE SOFTENING OR MELTING. MOLTEN MATERIAL CAN CAUSE SEVERE BURNS & EMIT IRRITATING FUMES. SLIPPERY WHEN WET.												

<b>SECTION V – Reactivity Data</b>							
Stability	Unstable	<b>NO</b>	Conditions to Avoid		<b>HEAT, SPARKS AND FIRE MATERIAL EXPOSED TO AIR WILL ABSORB MOISTURE.</b>		
	Stable	<b>YES</b>					
Incompatibility (Materials to Avoid)	<b>STRONG OXIDIZING AGENTS, ACIDS AND BASES</b>						
Hazardous Decomposition or By-Products	<b>THERMAL DECOMPOSITION MAY RESULT IN THE FORMATION OF TOXIC OXIDES OF CARBON.</b>						
Hazardous Polymerization	May Occur	<b>NO</b>	Conditions to Avoid		<b>NONE</b>		
	Will Not Occur	<b>YES</b>					
<b>SECTION VI – Health Hazard Data</b>							
Route of Entry		Inhalation?	<b>YES,POSSIBLY AS DUST</b>	Skin?	<b>YES</b>	Ingestion?	<b>UNLIKELY</b>
Heath Hazards (Acute and Chronic) Cut/Shredded Pads ONLY	<b>INHALATION: NO SPECIFIC INFORMATION. A RELATED PRODUCT HAS SHOWN EXPOSURE TO LOW LEVELS OF AIRBORNE DUST CAN RESULT IN LUNG IRRIATION AND INFLAMMATION. EYES: MAY CAUSE SLIGHT TO MODERATE IRRITATION. SKIN: MAY CAUSE SLIGHT IRRITATION. PROLONGED OR REPEATED EXPOSURE UNLIKELY TO CAUSE SIGNIFICANT IRRITATION. MOLTEN POLYOLEFIN COMPONENTS CAN CAUSE BURNS.</b>						
Carcinogenicity		NTP?	<b>NO</b>	IARC Monographs?	<b>NO</b>	OSHA Regulated?	<b>NO</b>
Signs and Symptoms of Exposure Cut/Shredded Pads ONLY	<b>EYE, NASAL OR BRONCHIAL IRRITATION; DRY SKIN WITH SLIGHT IRRITANT EFFECTS.</b>						
Medical Conditions Generally Aggravated by Exposure	<b>NONE KNOWN – CONTACT WEARERS MAY BE VERY SENSITIVE TO DUST AND EYE IRRITATION.</b>						
Emergency and First Aid Procedures	<b>SEEK MEDICAL ATTENTION IF CUT/SHREDDED PADS ARE SWALLOWED. WASH EXPOSED SKIN THOROUGHLY WITH SOAP &amp; WATER. FLUSH EXPOSED EYES WITH WATER FOR AT LEAST 15 MINUTES. REMOVE TO FRESH AIR IF OVEREXPOSED TO DUST. SEEK MEDICAL ATTENTION IN ALL CASES.</b>						
<b>SECTION VII – Precautions for Safe Handling and Use</b>							
Steps to be Taken in Case Material is Released or Spilled	<b>PADS SHOULD BE MOVED AND BAILED OR PLACED INTO CLOSED CONTANERS. AVOID GENERATION OF DUST. ELIMINATE IGNITION SOURCES. DO NOT APPLY WATER.</b>						
Waste Disposal Method	<b>APPROVED SOLID WASTE DISPOSAL IN ACCORDANCE WITH FEDERAL, STATE &amp; LOCAL REGULATIONS.</b>						
Precautions to be Taken in Handling and Storing	<b>STORE MATERIAL IN A DRY LOCATION. KEEP MATERIAL IN CLOSED BAGS OR CONTAINERS TO PREVENT ABSORPTION OF MOISTURE. AVOID SKIN &amp; EYE CONTACT.</b>						
Other Precautions	<b>CAUTION: PADS WILL ABSORB WATER &amp; BECOME SLIPPERY WHEN WET.</b>						
<b>SECTION VIII – Control Measures</b>							
Respiratory Protection (Specify Type)	<b>USE NIOSH/MSHA APPROVED RESPIRATORS WHEN DUST LEVELS EXCEED EXPOSURE LIMITS</b>						
Ventilation	Local Exhaust	<b>PROVIDE TO CONTROL AIRBORNE DUST</b>			Special	N/A	
	Mechanical (General)	<b>PROVIDE TO CONTROL AIRBORNE DUST</b>			Other	N/A	
Protective Gloves	<b>IMPERVIOUS GLOVES RECOMMENDED</b>			Eye Protection	<b>CHEMICAL SAFETY GOGGLES RECOMMENDED</b>		
Other Protective Clothing or Equipment	<b>DO NOT WEAR CONTACTS</b>						
Work/Hygienic / Maintenance Practices	<b>CLOTHING TO COVER EXPOSED AREAS. EYE WASH FOUNTAIN RECOMMENDED. PRACTICE GOOD HOUSEKEEPING. CAUTION: DO NOT GENERATE DUST FROM CUT/SHREDDED PADS. WET PADS BECOMES VERY SLIPPERY.</b>						